



DD/5



- Frontale e Porta 10 mm
- Taglio Laser

- Front and Door 10 mm
- Laser Cut



CERTIFICATA A  
NORMA EUROPEA  
UNI EN 14450-S2

CERTIFIED TO  
EUROPEAN STANDARD  
EN 14450-S2



EVO-LOCK



### Double-Bitted Key + 3 Counters Combination

- Latest generation high security lock, EN 1300 certified, with 8 asymmetrical and independent levers.

*It is based upon the use of new antipicking oscillating levers and mentonnet with special profile to oppose exceptional resistance to assaults with the latest sophisticated tamper systems using special picklocks, ex. "bulgarian tool".*

- Double-bitted key with special profile, duplicable with the ownership card, to prevent unauthorized key duplication.
- Combination block with 3 recessed handwheels of 20 positions each.
- Key-retaining lock in open position.
- Nickel-plated rotating steel bolts  $\varnothing$  22 mm.
- Lock mechanism protected by a manganese-steel plate.
- Special door battens for exceptional resistance against robbery attempts using a sledge hammer.
- Internally welded by a robotcontrolled system.
- Front panel seam-welded to the casing by a robot controlled system.
- Removable internal shelf.
- Anchor tongues on the 4 backs sides against jerks-attempts.
- Oven dried thermo-hardening powder painting.

Art Code	Misure esterne mm.			Misure interne mm.			Dim. porta mm.		Numero catenacci			Peso	Litri
	Alt/H	Larg/W	Prof/D	Alt/H	Larg/W	Prof/D	Alt/H	Larg/W	Oriz/Horiz	Vert		Kg	Lt
DD/3B	210	340	150	185	315	100	140	250	2	-	-	12,5	6,5
DD/3	210	340	200	185	315	150	140	250	2	-	-	13	9
DD/4	270	390	200	245	365	150	195	300	2	1+1	-	18	14
DD/4L	270	390	240	245	365	190	195	300	2	1+1	-	19	18
DD/5	340	460	200	315	435	150	265	370	3	1+1	-	25	21
DD/5L	340	460	240	315	435	190	265	370	3	1+1	-	26	27
DD/6	420	480	230	395	455	180	345	390	3	2+2	-	33,5	33
DD/6L	420	480	280	395	455	230	345	390	3	2+2	-	34,5	43
DD/7	480	420	280	455	395	230	405	330	3	2+2	-	34,5	43
DD/7L	480	420	360	455	395	310	405	330	3	2+2	-	37	57